Appln. S.N. 10/699,456 Response dated May 4, 2007

Reply to Office Action of February 6, 2007

Docket No. 100200584-1

In the claims:

1. (Previously presented) A fuel cell, comprising:

a substrate; and

a patterned film established on the substrate, the patterned film having a plurality of nanowires dispersed therein;

wherein the plurality of nanowires enhances catalytic activity and conductivity of the patterned film.

- 2. (Original) The fuel cell as defined in claim 1 wherein the plurality of nanowires increases the number of sites per unit volume where catalysis takes place.
- 3. (Original) The fuel cell as defined in claim 1 wherein the substrate is an electrolyte.
- 4. (Original) The fuel cell as defined in claim 3 wherein the electrolyte is at least one of oxygen ion conducting membranes, proton conductors, carbonate (CO_3^{2-}) conductors, OH^- conductors, cubic fluorite structures, doped cubic fluorites, proton-exchange polymers, proton-exchange ceramics, yttria-stabilized zirconia, samarium doped-ceria, gadolinium doped-ceria, $La_aSr_bGa_cMg_dO_{3-\delta}$, and mixtures thereof.
- 5. (Original) The fuel cell as defined in claim 1 wherein the substrate is at least one of single crystal silicon, polycrystalline silicon, silicon oxide containing dielectric substrates, alumina, sapphire, ceramics, cermets, anode materials, cathode materials, current collector materials, and mixtures thereof.
- 6. (Original) The fuel cell as defined in claim 1 wherein the plurality of nanowires is formed from at least one of carbon, copper, nickel, platinum, gold, iron, alloys thereof, stainless steel, lanthanum strontium chromite, current collector materials,

Appln. S.N. 10/699,456

Response dated May 4, 2007

Reply to Office Action of February 6, 2007

Docket No. 100200584-1

electrode materials, catalyst materials, electrolyte filament materials, and mixtures thereof.

3

- 7. (Original) The fuel cell as defined in claim 6 wherein the current collector material comprises high temperature metals.
- 8. (Original) The fuel cell as defined in claim 7 wherein the high temperature metals are at least one of gold, copper, stainless steel, nickel alloys, and mixtures thereof.
- 9. (Previously presented) The fuel cell as defined in claim 1 wherein the patterned film comprises an anode.
- 10. (Original) The fuel cell as defined in claim 9 wherein the plurality of nanowires comprises metallic components of anode material.
- 11. (Original) The fuel cell as defined in claim 10 wherein the anode metallic components comprise at least one of nickel-copper alloys, platinum, palladium, ruthenium, alloys thereof, and mixtures thereof.
- 12. (Previously presented) The fuel cell as defined in claim 1 wherein the patterned film comprises a cathode.
- 13. (Original) The fuel cell as defined in claim 12 wherein the plurality of nanowires comprises metallic components of cathode material.

Appln. S.N. 10/699,456 Response dated May 4, 2007

Reply to Office Action of February 6, 2007

Docket No. 100200584-1

- 14. (Original) The fuel cell as defined in claim 13 wherein the cathode metallic components comprise at least one of rhodium, platinum, silver, alloys thereof, and mixtures thereof.
- 15. (Previously presented) The fuel cell as defined in claim 1 wherein the plurality of nanowires is randomly oriented throughout the patterned film.
- 16. (Original) The fuel cell as defined in claim 1 wherein the plurality of nanowires has a diameter ranging between about 1 nm and about 100 nm.
- 17. (Original) The fuel cell as defined in claim 1 wherein the plurality of nanowires has a diameter ranging between about 10 nm and about 50 nm.
- 18. (Original) The fuel cell as defined in claim 1 wherein the plurality of nanowires has a length ranging between about 15 nm and about 2000 nm.
- 19. (Original) The fuel cell as defined in claim 1 wherein the plurality of nanowires has a length ranging between about 100 nm and about 500 nm.
 - 20. (Original) An electronic device, comprising:

a load; and

the fuel cell of claim 1 connected to the load.

- 21 47. (Canceled)
- 48. (Previously presented) A method of using a fuel cell, comprising the step of:

5

Appln. S.N. 10/699,456 Response dated May 4, 2007 Reply to Office Action of February 6, 2007

Docket No. 100200584-1

operatively connecting the fuel cell to at least one of an electrical load and an electrical storage device, the fuel cell comprising:

a substrate; and

a patterned film established on the substrate, the patterned film having a plurality of nanowires dispersed therein;

wherein the plurality of nanowires enhances catalytic activity and conductivity of the patterned film.

49. (Previously presented) A fuel cell, comprising:

a substrate;

a patterned film established on the substrate; and

means, dispersed throughout the patterned film, for substantially enhancing catalytic activity and conductivity throughout the patterned film.

50 - 67. (Canceled)

- 68. (Previously presented) The fuel cell as defined in claim 1 wherein the fuel cell is a single chamber fuel cell.
- 69. (Previously presented) The fuel cell as defined in claim 1 wherein the plurality of nanowires is connected to at least one of catalytic nano-particles or electrolyte grains.
- 70. (Previously presented) The fuel cell as defined in claim 1 wherein the plurality of nanowires is formed from electrolyte filament materials, and wherein the fuel cell further comprises cathode material nanoparticles dispersed on and connected to the electrolyte filament material nanowires.

Appln. S.N. 10/699,456 Response dated May 4, 2007 Reply to Office Action of February 6, 2007 Docket No. 100200584-1

71. (Previously presented) The fuel cell as defined in claim 1 wherein the fuel cell is a solid oxide fuel cell.

6